

Sockets for domestic applications

No. REFERENCE SERIES

570


VERSIONS


 Panel mounting
 flange 50x60mm
 IP44

 Panel mounting
 flange 70x87mm
 IP44

 Panel mounting
 flange 70x87mm
 IP44

 Surface mounting
 flange 70x87mm
 IP44

REFERENCE STANDARDS

 Standards: **CEI 23-50**
NFC 61-303
VDE 0620

MARKING



 Marking: **CE Marking**


QUALITY MARKS



TECHNICAL CHARACTERISTICS

Rated current: **16A**
 Rated voltage: **250V~**
 Frequency: **50Hz**
 Insulating voltage: **690V~**
 Protection degree: **IP44 closed cover**
 Operating temperature according to the reference standard: **-25°C+35°C**
 Max operating temperature: **60°C**
 Glow Wire test: **650°C/750°C**
 Material: **Engineering plastic**
 IK degree at 20°C: **IK06**
 Cabling capacity of the terminals: **1,5mmq ÷ 2x2,5mmq**



BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
RESISTANT	NOT RESISTANT	NOT RESISTANT	LIMITED RESISTANCE	RESISTANT	NOT RESISTANT	NOT RESISTANT	NOT RESISTANT	LIMITED RESISTANCE	RESISTANT	RESISTANT